



Also available in  
SKF SYSTEM 24



Designed to fulfill the requirements of most industrial chain applications

## SKF Chain Oil

### LHMT 68

SKF LHMT 68 is ideal for medium temperatures and dusty environments like those of cement and material handling industries, where a high penetration and light film are required.

### LHHT 265

SKF LHHT 265 synthetic oil is ideal for high load and/or high temperature conditions, like those found in the pulp and paper and textile industries. It doesn't form any residue at high temperatures and it is neutral towards seals and polymers.

### Benefits

- Increase chain life
- Increase re-lubrication interval
- Reduce oil consumption
- Reduce energy consumption

### Typical applications:

- Conveyor chains
- Drive chains
- Lift chains



## Technical data

Designation	LHMT 68	LHHT 265
Description	Medium temperature oil	High temperature oil
Specific gravity	0.85	0.92
Colour	Yellowish brown	Yellow orange
Base oil type	Mineral	Synthetic ester
Operating temperature range	-15 to +90 °C (5 to 194 °F)	Up to 250 °C (482 °F)
Base oil viscosity:		
40 °C (104 °F), mm <sup>2</sup> /s	ISO VG 68	approx. 265
100 °C (212 °F), mm <sup>2</sup> /s	approx. 9	approx. 30
Flash point	>200 °C (392 °F)	approx. 260 °C (500 °F)
Pour point	<-15 °C (5 °F)	n/a
NSF approval	n/a	n/a

## Ordering details

Chain oil	LHMT 68	LHHT 265
Description	Medium temperature oil	High temperature oil
Can 5 liter	LHMT 68/5	LHHT 265/5

## SKF SYSTEM 24

LAGD series	Unit 60 ml	LAGD 60/HMT68*	—
	Unit 125 ml	LAGD 125/HMT68*	LAGD 125/HHT26*
LAGE series	Complete unit 122 ml	LAGE 125/HMT68	LAGE 125/HHT26
	Complete unit 250 ml	LAGE 250/HMT68	LAGE 250/HHT26
	Refill set 122 ml	LHMT 68/EML125	LHHT 265/EML12
	Refill set 250 ml	LHMT 68/EML250	LHHT 265/EML25

\* Includes non-return valve

© SKF is a registered trademark of the SKF Group.

© SKF Group 2011

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

PUB MP/P8 12040 EN · November 2012

