

LGMT 2

SKF General Purpose Industrial and Automotive Bearing Grease

SKF LGMT 2 is mineral oil based, lithium soap thickened grease with excellent thermal stability within its operating temperature range. This premium quality, general purpose grease is suitable for a wide range of industrial and automotive applications.

- Excellent oxidation stability
- Good mechanical stability
- Excellent water resistance and rust inhibiting properties

Typical applications:

- Agricultural equipment
- Automotive wheel bearings
- Conveyors
- Small electric motors
- Industrial fans



Technical data

Designation	LGMT 2/(pack size)	
DIN 51825 code	K2K-30	
NLGI consistency class	2	
Soap type	Lithium	
Colour	Red brown	
Base oil type	Mineral	
Operating temperature range	-30 to +120 °C (-20 to +250 °F)	
Dropping point DIN ISO 2176	>180 °C (>355 °F)	
Base oil viscosity	40 °C, mm ² /s	110
	100 °C, mm ² /s	11
Penetration DIN ISO 2137:	60 strokes, 10 ⁻¹ mm	265-295
	100 000 strokes, 10 ⁻¹ mm	+50 max. (325 max.)
Mechanical stability	Roll stability,	
	50 hrs at 80 °C, 10 ⁻¹ mm	+50 max.
	V2F test	'M'

Corrosion protection		
Emcor:		
- standard ISO 11007		0-0
- water washout test		0-0
- salt water test (100% seawater)		0-1*
Water resistance		
DIN 51 807/1,		
3 hrs at 90 °C		1 max.
Oil separation		
DIN 51 817,		
7 days at 40 °C, static, %		1-6
Lubrication ability		
R2F,		
running test B at 120 °C		Pass
Copper corrosion		
DIN 51 811, 110 °C		2 max. at 130 °C (265 °F)
Available pack sizes		
		35, 200 g tube
		420 ml cartridge
		1, 5, 18, 50, 180 kg

* Typical value



SKF lubricants offer major competitive advantages:

- Designed and tested to outperform under real conditions
- Product data include specific test results enabling a better selection
- Strict quality control of every production batch help ensure consistent performance
- Quality control allows SKF to offer a five-year shelf-life* from the date of production



Production processes and raw materials vastly influence grease properties and performance. It is virtually impossible to select or compare greases based only on their composition. Therefore, performance tests are needed to provide crucial information. In over 100 years, SKF has accrued vast knowledge about the interaction of lubricants, materials and surfaces.



This knowledge has led SKF, in many cases, to set industry standards in bearing lubricant testing. Emcor, ROF, ROF+, V2F, R2F and Bequiet are just some of the multiple tests developed by SKF to assess the performance of lubricants under bearing operating conditions. Many of them are widely used by lubricant manufacturers worldwide.

* SKF LGFP 2 food grade grease offers a two-year shelf-life from the date of production

© SKF is a registered trademark of the SKF Group.

© SKF Group 2011

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

PUB MP/P8 12018 EN · July 2011

